

graboSport MEGA

Property	Standard	Unit	Result
----------	----------	------	--------

DESCRIPTION			
Surface	-	-	TECH Surface
Backing	-	-	Closed cell combined foam
Thickness	EN ISO 24346	mm	10
Weight	EN ISO 23997	kg/m ²	5,3
Width	EN ISO 24341	m	2
Standard roll length	EN ISO 24341	m	13
Maximal roll length	EN ISO 24341	m	15

CLASSIFICATION			
Product specification	Vinyl indoor sports floor	EN 14904 (category P2)	
Thermal resistance	-	m ² K/W	0,10
Reaction to fire	EN 13501	-	C _{fl} -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

SPORT PROPERTIES			
Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	38
Vertical deformation	EN 14809	mm	1,5
Ball rebound	EN 12235	%	97
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS			
Dimensional stability	EN ISO 23999	%	± 0,2
Indentation resistance	EN 1516	mm	<0,5
Resistance to rolling load	EN 1569	N	1500
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN ISO 26987	-	no change
Abrasion resistance	EN ISO 5470-1	mg/1000cycles	< 250

OTHERS		
Limited warranty		15 years
Cleanability		TECH Surface - Easy to clean
Antimicrobial treatment		graboSAN
Environmental attributes		No periodic renewal needed Solvent and heavy metal free

GRABOPLAST Floor Covering Manufacturers Ltd.
H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100
mail@graboplast.hu www.graboplast.hu